

DOP- 07

1. Unique identification code of the product-type: POLICAM POLICARBONATE SOLID SHEET-6MM CLEAR
2. Intended use/es : Internal and external wall and ceiling finishes
3. Manufacturer : İSİK PLASTİK SAN. ve DIS. TIC. PAZ. A.S
4. Authorised representative : Not relevant
5. System/s of AVCP : System 3
- 6a. Harmonised standard : EN 16240:2013
Notified body/ies : EFECTIS ERA AVRASYA –2184
- 6b. European Assessment Document :
European Technical Assessment :
Technical Assessment Body :
Notified body/ies :
7. Declared performance/s

Essential characteristics <i>Temel Karakteristikler</i>	Performance <i>Performans</i>
External fire performance <i>Harici Yangın Performansı</i> EN 13501-5	NPD
Reaction to fire <i>Yangına Karşı Tepki</i> EN 13501-1	B S1 d 0
Resistance to fire <i>Yangına Dayanım</i> EN 13501-2	NPD
Water vapour permeability <i>Su buharı geçirgenliği</i> EN ISO 12572.	$3,8 \cdot 10^{-5}$ mg/m h.Pa
Water/air permeability <i>Su/Hava Geçirgenliği</i>	PASS

Release of dangerous substances <i>Tehlikeli madde salınımı</i>	NPD
Dimensional tolerances <i>Boyutsal toleranslar</i>	Thickness : ± 5 % equal to 2mm and up or equal to 5mm. / ± 10 % greater than 5mm Length / Width : 0 % to + 0,30 % of the declared sheet length/width.
Shatter properties (safe breakability) as :	
-Small hard body impact resistance	PASS
-Large body impact resistance (assembly)	NPD
Mechanical resistance (deformation behaviour) <i>Mekanik direnç</i>	$E_f, \text{mean} = 2200 \text{ N/mm}^2$ $E_f, \text{charac} = 2000 \text{ N/mm}^2$ $\sigma_M, \text{mean} = 60 \text{ MPa}$ $\sigma_M, \text{charac} = 55 \text{ MPa}$
Direct airborne sound insulation <i>Havadaki ses yalıtımı</i>	$R = 28 (0;-3) \text{ dB}$
Thermal transmittance <i>Isıl geçirgenlik</i>	$5,0 \text{ W/m}^2 \cdot \text{K}$
Light transmittance	$T_v = 85,5 \%$
Total solar energy transmittance	$T_e = 75,8 \%$ $g = 81,6 \%$
Resistance to fixings	Method of fixing (see manufacturer's datasheet)
Durability, as variation (after ageing)	NPD

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name] : Burak Koçak / QA Manager

At [place] : Mustafapasa mah. İhsan Dede cad No:101 Gebze - KOCAELİ /TÜRKİYE

on [date of issue] : 01.12.2024

[signature] : 
Işık Plastik San. ve Tic. Paz. A.Ş.
G.O.S.B. İhsan Dede Cad. No: 101 Gebze
Marmara Kurumlar Y.D. 083 2685 Kocaeli
Tel: 0 262 751 22 35 Fax: 0 262 751 22 40